

GO4STAGE CHAIN HOISTS

250KG-2000KG ELECTRIC CHAIN HOIST

G4-HT-0250-20 / G4-HT-0250-25 / G4-HT-0500-20 / G4-HT-0500-25 / G4-HT-1000-20
G4-HT-1000-25 / G4-HT-2000-20 / G4-HT-2000-25

**preliminary*



PRODUCT DESCRIPTION

Professional electric chain hoist engineered for entertainment, stage, and industrial lifting applications. Designed according to D8Plus principles with dual brake system, enhanced safety features, low-noise operation, and robust aluminum housing.

KEY FEATURES

- Dual independently acting DC brakes (operating brake + safety brake);
- Closed-circuit current brake system with automatic load holding during power failure;
- Friction clutch protection system;
- Optional overload and underload monitoring;
- Compact fully enclosed cast aluminum housing;
- Low-noise operation: 50 dB(A) at 1 meter;
- High-strength EN818-7 profile steel chain;
- Textile chain bag with optimized hanging structure;
- Soft start & stop functionality;
- Enhanced surface treatment with bake-hardened paint finish;
- Safety factor up to 8:1 static load compliance;
- German-designed motor with constant output power;

TECHNICAL SPECIFICATIONS

CAPACITY	MOTOR POWER	SPEED	CHAIN SIZE	PROTECTION	FEM/ISO	NOISE LEVEL
250 kg	0.23 kW	4 m/min	5×15 mm	IP66	2m/M5	50 dB(A)
500 kg	0.45 kW	4 m/min	6.3×19 mm	IP66	2m/M5	50 dB(A)
1000 kg	1.30 kW	4 m/min	8×24 mm	IP66	2m/M5	50 dB(A)
2000 kg	2.50 kW	4 m/min	12×36 mm	IP66	2m/M5	50 dB(A)
3000 kg	4.80 kW	4 m/min	16×48 mm	IP66	2m/M5	50 dB(A)

APPLICATIONS

Suitable for entertainment rigging, stage productions, concerts, theaters, exhibitions, and industrial lifting operations.

Specifications subject to change without notice.

DIMENSIONS

MODEL	W	H	E	D	NO CHAIN WEIGHT	WEIGHT PER METER OF CHAN
250 kg	290	345	186	109	14.5kg	0.54kg/m
500 kg	341	350	226	121	22.0kg	0.85kg/m
1000 kg	406	380	247	135	38.9kg	1.33kg/m
2000 kg	475	725	425	224	123kg	3.1kg/m
3000 kg	646	886	534	378	225kg	5.63kg/m